



GMF7522IXL

75CM 5 BURNER GAS COOKTOP



FEATURES & BENEFITS



IXLIUM

Whirlpool introduces an innovative material aimed at all those who love design, but hate cleaning. Thanks to an exclusive nano-technology treatment, the iXelium cooktop is extremely easy to clean. Unlike a standard steel top, iXelium prevents food residuals from sticking to the surface so all you need to do to remove dirt is a soft sponge and non aggressive detergent. The result is a cooking surface which will remain shiny over time without scratches.




HIGH EFFICIENCY BURNERS

This model features 5 unique vertical flame burners that enable fast cooking, while at the same time decreasing energy consumption and CO2 emissions.




POWERFUL RAPID BURNER

Whirlpool's high powered rapid burner is included for extra strength cooking.



CAST IRON TRIVETS & WOK SUPPORT

Traditional Cast Iron for a premium finish, durability and long lasting quality features, including Wok Support.



LASER ETCHED SERIGRAPHY

The sleek design includes laser etched serigraphy on control panel settings and logo.



WARRANTY

Guarantees peace of mind and value for money knowing that any product fault or defect is covered by full replacement parts and/or a service call to ensure the product works as described.

TECHNICAL SPECIFICATIONS

MAIN COLOUR FINISH	Stainless Steel Ixelum
PRODUCT DIMENSIONS	W 730mm x H 41mm x D 510mm
CUT OUT DIMENSIONS	W 560mm x H 38mm x D 480mm
PACKAGE DIMENSIONS	W 770mm x H 155mm x D 595mm
BURNERS	5, Black
CONTROLS	5 Front Knobs
TRIVETS	3 Cast Iron
IGNITION	Electric
SAFETY	Flame Failure
ELECTRICAL RATING	10amps
ELECTRICAL CONNECTION	Plug and Supplied
INSTALLATION	Built-In
NET WEIGHT	14.2kg
ACCESSORIES INCLUDED	LPG Jets Included, Cast Iron Trivets and wok support
WARRANTY	5 years

BURNER SPECIFICATIONS

FRONT RHS: AUXILIARY NPG: Pressure, Injector & Rate ULPG: Pressure, Injector & Rate	Pot Size: 8cm to 14cm 1.00kPa, 0.90mm & 3.60Mj/h 2.75kPa, 0.52mm & 3.60Mj/h
REAR RHS: SEMI-RAPID NPG: Pressure, Injector & Rate ULPG: Pressure, Injector & Rate	Pot Size: 16cm to 22cm 1.00kPa, 1.17mm & 6.30Mj/h 2.75kPa, 0.67mm & 6.30Mj/h
REAR LHS: RAPID NPG: Pressure, Injector & Rate ULPG: Pressure, Injector & Rate	Pot Size: 24cm to 26cm 1.00kPa, 1.40mm & 10.80Mj/h 2.75kPa, 0.85mm & 10.80Mj/h
REAR LHS: SEMI-RAPID NPG: Pressure, Injector & Rate ULPG: Pressure, Injector & Rate	Pot Size: 16cm to 22cm 1.00kPa, 1.17mm & 6.30Mj/h 2.75kPa, 0.67mm & 6.30Mj/h
FRONT LHS: 2 CROWN NPG: Pressure, Injector & Rate ULPG: Pressure, Injector & Rate	Pot Size: 24cm to 26cm 1.00kPa, 1.92mm & 17.28Mj/h 2.75kPa, 1.08mm & 17.28Mj/h

DISTRIBUTED BY ARISIT PTY LTD

40-50 Mark Anthony Drive, Dandenong South VIC 3175
Ph: 1300 762 219 Fax: 03 9768 0838 Website: www.arisit.com